

2006 PRE-USE TACTICAL WATER TENDER INSPECTION FORM

Company Name:		Date:	
<u>Vehicle Identification</u>			
NWCG Type Tactical Water Tender (1-3):		Allowable Tank Capacity (gallons)	
VIN #:		DOT #:	
License #:	State:	Unit ID #:	
Make:	Model:	Year:	
<u>Vehicle Licensing</u>		<u>Satisfactory?</u>	
		Yes	No
Vehicle meets licensing requirements			
Operator meets CDL licensing requirements with Tank Endorsement			
Vehicle meets insurance requirements			
Vehicle meets CVSA requirements (optional)			
<u>Individual Training Information</u>		<u>Satisfactory?</u>	
		Yes	No
Photo Identification Card for each crewmember			
Annual Fireline Refresher Training			
WCT		Pass	Fail
<u>Red Card Rating</u>			
ENG OP		FF2	
<u>Personal Protective Equipment</u>		Yes	No
		Qty	
Boots, leather lace up w/lug sole, 8" tops, no steel shank			
Hardhat, plastic, 1 per person, OSHA approved			
Gloves, 1 pair per person, all leather			
Goggles, 1 pair per person			
Flame resistant clothing, (shirt and trousers)			
Head Lamp, 1 lamp per person w/batteries & hardhat attachment			
Canteen, 2 per person, 1 quart size			
Fire Shelter, 1 per person			
<u>Minimum Tender Inventory</u>		<u>Satisfactory?</u>	
		Yes	No
		Qty	
Dump Valve rear of tank, 4" min. 34" from ground to outlet			
2-1/2" valve at bottom of tank with nh hose threads			
Fuel to operate for 12 hours (pump and tender)			
Hydrant Wrench, 1 each			
Fire Hose Clamp, 1 each			
Spanner wrench suitable for each size hose supplied			
1 – Hand held programmable radio with 2 additional batteries or rechargers			
<u>Pressurized discharge outlets:</u>			
A. 2-1/2" nh			
Type 1: 2 each			
Type 2 & 3: 1 each			
B. 1-1/2" nh			
Type 1: 1 each			
Type 2 & 3: 2 each			
<u>Hose</u>			
A. Live Hose Reel with min. 100' of 1" hose			
B. 200' of 1-1/2"			
C. 50' of 2-1/2"			

2006 PRE-USE TACTICAL WATER TENDER INSPECTION FORM

Company Name:		Date:	
Nozzle		Satisfactory?	
		Yes	No
A. 1-1/2" combination fog/straight stream			
Adapters			
2 – 2-1/2" nh double female			
2 – 2-1/2" nh double male			
2 – 2-1/2" to 1-1/2" nh reducer			
Pumps			
Type of Pump and Size:		Serial #:	
Pump meets NWCG requirements in Appendix "E"		Yes	No
24' Suction hose w/strainer or screened foot valve w/ hole size of 3/32" or less			
Foam Proportioner System (Type)		Yes	No
If Yes checked for Foam Proportioner System amount of foam carried on engine in gallons:			
Additional Vehicle Safety Items		Satisfactory?	
		Yes	No
Reflective Triangles, bi-directional, set of 3			
Fire Extinguisher, 1 rated at 5 B:C or better OR 2 rated at 4 B:C			
Chock Blocks, 2			
1 – Shovel, size "0"			
1 – Pulaski			
Seat Belt for all passengers		Yes	No
Vehicle Tires		Satisfactory?	
		Yes	No
Tire load ratings in accordance with vehicle GVWR			
All season mud and snow tread with minimum 1/4" tread			
Vehicles with 4-wheel drive have mud and snow tread on all wheels			
Full size spare tire and wheel with changing equipment that shall fit any position or a spare tire for front and rear axle			
Vehicle Condition			
Glass (chips/cracks)			
Body Condition (dents/scratches)			
Name of Contractor (type or print)		Signature of Contractor	
Name of Inspector (type or print)		Signature of Inspector	
Inspectors' Agency		Inspector's Phone #	